

Product Name: Amina Shoe & Thazo Boot  
Product Description: Sheba Ladies Leather Shoe & Boot  
Product Code: GL0910 (Shoe) or GL0911 (Boot)

REBEL

SAFETY GEAR

AFRICA'S HARDEST WORKING BOOTS



Materials

CE EUROPEAN STANDARD: EN ISO 20345:2004



Upper	High Quality Full Grain Cow Leather	Toe Cap	Wide Profile Carbon Steel
Inner Sole	Biagioli IBITECH 252 2mm Foam Insole Board	Eyelet	GL0910: Slip-On Elasticated construction
Lining	Breathable and Abrasion Resistant Tai-brella (Equivalent to Cambrelle)	Sole	GL0911: Easy Zip-up design
			Dual Density Poly Urethane Sole

Specifications

Specifications	<ul style="list-style-type: none"><li>European Norm EN ISO 20345-S1</li><li>Tested by SATRA - Approved Body Identification Number : 0321</li></ul>
Special Features	<ul style="list-style-type: none"><li>Easy elasticated slip-on design on shoes</li><li>Boots have easy zip-up design</li><li>Sole has 2-tiered heel design without compromising safety</li><li>Dual-density PU Sole ensures maximum comfort and increased durability</li></ul>
Sole	<ul style="list-style-type: none"><li>Temperature Maximum 90°C (degrees Celsius)</li><li>Oil and acid resistant PU/Rubber</li><li>Slip Resistance - Tested to SATRA PM144 1992 and meets these requirements</li><li>However, care should always be taken on wet or oily surfaces</li><li>Crack Resistance - Tested to 30,000 flex cycles</li></ul>
Toe Cap	<ul style="list-style-type: none"><li>Tested to an impact resistance of 200 Joules</li></ul>
Water Applications	<ul style="list-style-type: none"><li>Water resistant - Leather and PU combination</li></ul>
Anti Static Properties	<ul style="list-style-type: none"><li>Product is anti static. If application is life critical additional consultation with product expert is required. Electrical resistance can be significantly changed by flexing, contamination or moisture. Introduction of additional inner sole reduces static resistance</li></ul>
Sizing	<ul style="list-style-type: none"><li>Available from Size 2 to Size 8 (Ladies)</li></ul>
Lifespan	<ul style="list-style-type: none"><li>The application determines the length of service that should be achieved. Normal environments should provide 12 months' service, if appropriate care is taken. Refer Care guidelines</li></ul>

Uses

Suitability

Comments

General	Highly suitable	
Construction	Widely used	
Mining	Widely used	Care in very wet areas required. Gumboots would be more suitable for wet area applications
Petrochemical	Widely used	Highly oil resistant but reference to chemical chart below is recommended
Engineering	Highly suitable	
Power Generation	Widely used	
Agriculture	Highly suitable	
Food & Health	Widely used	Reference to Chemical resistance in cleaning areas may be necessary
Fishing & Allied Industries	Widely used	
Fabrication	Highly suitable	
Metal Industries	Widely used	Temperature limitations must be observed
Motor Industry	Highly suitable	
Glass Manufacturing & Fabrication	Widely used	Steel midsole advised to protect against glass penetration of the sole (Refer to: RE608-S3 & FX2-S1P)
Municipality	Highly suitable	
Waste Disposal	Widely used	Steel midsole advised to protect against penetration of the sole (Refer to: RE608-S3 & FX2-S1P)
Civil Contracting	Widely used	
Moving and Rigging	Highly suitable	
Forestry	Widely used	
Telecommunications	Widely used	In the appropriate job requirement
Contract Labour	Highly suitable	
Transport - Air, Road & Rail	Widely used	
Transport - Shipping	Widely used	

It is important that the footwear selected must be suitable for the protection required by the wearer and the environment. If any uncertainty exists consultation between buyer and seller should be conducted to ensure that the correct footwear is selected. This application guide only offers very general advice and should be confirmed if there may be any concerns over potential protection from hazards of any form.

To view the complete REBEL Safetygear range, please visit: [www.rebelsafetygear.com](http://www.rebelsafetygear.com)